

L20/540 - SLIDING FOLDING PARTITIONS TO

Refer to drawings:

Manufacturer and reference: Series 200 Sliding Partition by Brockhouse Modernfold Limited

Kay One,
23 The Tything,
Worcester,
WR1 1HD
01905 330055
01905 330234

Characteristics: 61/68/100mm thick manually operated flat panel continuously hinged system with internal espagnolette locking mechanism (external footbolts are not acceptable). Panels are connected by full length piano hinges (butt hinges not acceptable). All systems are supplied as standard with 2 No. three pronged rubber sweep seals at the top and bottom of each panel and vertical 'D' seals in side profile.

Colour/Finishes: _____ (Range includes: veneer, laminate, melamine, paint to RAL/NBS spec, priming sheet for decoration, vinyl)

Furniture: Flush D-ring door handle, cylinder lock provided on request, removable locking handle for alternate standard panels.

Acoustic Rating: Rw 25 / 36 / 39 / 42 / 45 / 48 dB in accordance with ISO 140 Part 3

Track and Roller System: Top Hung, heavy duty extruded aluminium track with white pelmets. With/without floor tracks. Endfold / Centrefold.

Track and Roller System: Floor Mounted, SAA aluminium floor track with top guide rail, provided with white pelmets. Endfold / Centrefold.