

BROCKHOUSE MODERNFOLD SERIES 215F

TECHNICAL SPECIFICATION

PROJECT: -----

Characteristics: Top hung continuously hinged sliding folding partition. All systems made to measure to suit actual site dimensions. All systems are supplied as standard with sweep seals at the top and bottom of each panel. Wall posts supplied to match finish of partition as standard. System comes complete with a full height pass door with level handle Assa 696, subject to panel configuration.

Construction: Timber frame clad with high density particle board. Acoustic materials, including 6mm glass fibre reinforced plasterboard. Panels incorporate vertical vinyl 'D' seals.

Operation: Manually operated flat panel hinged system with internal espagnolette locking mechanism (external footbolts are not acceptable).

Track & Roller System:

Top Hung with no floor track (centrefold only) aluminium head track clad with 19mm fire retardant 'Securit' material.

Opening Size:
A) _____ mm x _____ mm
B) _____ mm x _____ mm
C) _____ mm x _____ mm

Finish: _____ (Range includes : veneer, laminate, melamine, paint to RAL/NBS spec, priming sheet for decoration, vinyl)

Acoustic Rating: Rw _____ dB (Range 39dB for half an hour to 42dB for 1 hour)

Stacking: Single wing / bi-parting
Centrefolding / Endfolding

Suspension: Top Hung

Edge Profiles: Hardwood lipping

Cylinder Lock: Yes / No

Supplier: **Brockhouse Modernfold Ltd**
Kay One,
23 The Tything,
Worcester,
WR1 1HD

Tel: **01905 330055**

Fax: **01905 330234**

E-mail: **sales@brockhouse.net**